

Pyrogel ® XT Plus Revision Date: 12/07/11

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Product Name: Pyrogel® XT Plus

Synonyms: Silica aerogel materials

Use of the Substance/Preparation: High performance insulation material

Manufacturer: Aspen Aerogels, Inc. Address: 30 Forbes Road

Northborough, MA 01532

Telephone: (508) 691-1111 Email: EHS@aerogel.com

Emergency Telephone Number: 800-535-5053 US & Canada (INFOTRAC)

352-323-3500 International

MSDS Prepared by: EHS

Phone Number of Preparer: 508-691-1111

2. HAZARDS IDENTIFICATION

Classification: Product is not classified as a dangerous material or preparation as defined in EC Directives

67/548/EEC or 1999/45/EC.

Emergency Inhalation of excessive amounts of dust from the product may cause mechanical irritation to the

Overview: respiratory tract. Dermal contact may cause mechanical irritation.

POTENTIAL HEALTH EFFECTS

Inhalation: Inhalation of airborne dusts may cause mechanical irritation of the upper respiratory tract.

Exposure to dust from this product can produce a drying sensation and mechanical irritation of

the eyes.

Skin Contact: Skin contact with dust from this product can produce a drying sensation and mechanical

irritation of the skin and mucous membranes.

Skin Absorption: Material will not absorb through skin.

Ingestion: This material is not intended to be ingested (eaten). If ingested in large quantity, the material

may produce mechanical irritation and blockage

Acute Health Dust from this product is a physical irritant, and may cause temporary irritation or scratchiness

Hazards: of the throat and / or itching and redness of the eyes and skin.

Chronic Health Per the fiberglass manufacturer, the fiberglass is considered textile grade and is not classified

Hazards: as a human carcinogenic by IARC (Group 3), ACGIH (Group A4), NTP, or OSHA...

as a numan carcinogenic by IARC (Group 3), ACGIH (Group A4), NTP, or OSHA..

Medical Conditions Excessive inhalation of dust may aggravate pre-existing chronic lung conditions including, but

Aggravated by not limited to, bronchitis, emphysema, and asthma. Dermal contact may aggravate existing

Exposure: dermatitis.

CARCINOGENICITY

Component	ACGIH	NTP	IARC
Natural Micaceous Iron Oxide	A4	Not Listed	None
Continuous Filament Glass Fibers	A4	Not Listed	3
Aluminum Trihydrate	Not Listed	Not Listed	None
Amorphous Silica	NA	Not Listed	None



Pyrogel ® **XT Plus Revision Date:** 12/07/11

SECTION 2 NOTES: This product is composed of synthetic amorphous silica dioxide. Amorphous silica should not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects from exposure to synthetic amorphous silica.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Percent	EINECS Number	EU Classification
Methylsilylated Silica	68909-20-6	40-50	272-697-1	None
Fibrous glass (textile grade)	NA	40-50	Not Assigned	None
Iron Oxide	1309-37-1	1-5	215-168-2	None
Aluminum Trihydrate	21645-51-2	1-5	244-492-7	None

4. FIRST AID MEASURES

Eye Contact: Immediately wash with large amounts of water for at least 15 minutes, occasionally lifting lids.

If irritation occurs and persists, get medical treatment.

Skin Contact: Wash skin thoroughly with soap and water until clean. The soap will act as a surfactant to

remove the material. Remove contaminated clothing and shoes. Wash clothing before reuse.

Obtain medical attention if symptoms occur.

Ingestion: Material will pass through the body normally. Obtain medical attention if symptoms occur.

Inhalation: Remove to fresh air. Drink water to clear throat and blow noise to remove dust. Obtain

medical attention if ill effects persist.

5. FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY PROPERTIES

Flammable	No
Auto ignition Temperature	Not Applicable
Flash Point	Not Applicable
Flammability Limits: (Lower Explosive Limit)	Not Applicable
Flammability Limits: (Upper Explosive Limit)	Not Applicable
Explosion Data – Sensitivity to impact	Not sensitive
Explosion Data – Sensitivity to static discharge	Not sensitive

5.2 EXTINGUISHING MEDIA:

Use media suitable for surrounding fire and that are appropriate to the surrounding environment; normal fog nozzle water application and/or exclusion of air is typically suitable for extinguishing this product in blanket form.

5.3 PROTECTION FOR FIRE FIGHTERS

Special Fire Fighting Procedures: Normal fire fighting procedures should be followed to avoid inhalation of smoke

and gases produced by a fire.

Unusual Fire and Explosion

Hazards:

Product is a super-insulation material. Rolls of material can retain heat within internal layers and re-ignite combustible materials if heat is not removed.

Hazardous Decomposition and/or

Combustion Products:

Primary combustion products are carbon monoxide and carbon dioxide. Other

undetermined products could be released in small quantities.



Pyrogel ® XT Plus Revision Date: 12/07/11

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Minimize dust generation. Ensure adequate ventilation. Use personal protective

equipment as necessary.

Environmental Precautions: Material is not soluble. Do not flush into surface water or sanitary sewer system.

Methods for Cleaning Up: Contain and collect released material for proper disposal. Dry vacuuming is the

preferred method of cleaning up.

7. HANDLING AND STORAGE

Handling Aerogel blankets will generate dust when handled. Workplace exposure to all dusts should be

controlled with standard industrial hygiene practices. Dry vacuuming is the preferred method for cleaning up dust. Because aerogel dust is hydrophobic, water is not effective as a dust control agent.

Storage Aerogel blankets should be kept in their packaging until they are ready to be used. Unpack the material

in the work area. This will help to minimize the area where dust exposure may occur. Trimmed

material and scrap should be promptly packed in disposal bags.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limit Values

There are no exposure limits identified for the main product component, classified as synthetic amorphous silica.

CAS Number	Component Name	Exposure Limits	
7631-86-9	Silica, Amorphous	Germany TRGS 900	4 mg/m ³ (inhalable fraction)
		UK WEL	6 mg/m ³ (total inhalable fraction) 2.4 mg/m ³ (respirable fraction)
		US OSHA PEL (TWA) ^a :	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
		US ACGIH ^b	10 mg/m ³ (inhalable)
			3 mg/m ³ (respirable)
1309-37-1	Iron Oxide	Germany TRGS 900	1.5 mg/m ³ (respirable dust)
		UK WEL	10 mg/m^3
		US OSHA PEL (TWA):	10 mg/m ³ (iron oxide fume) 5 mg/m ³ (respirable)
		US ACGIH:	5 mg/m (respirable)
21645-51-2	Aluminum Trihydrate	US OSHA PEL (TWA) ^a :	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
		US ACGIH ^b	10 mg/m ³ (inhalable)
			3 mg/m ³ (respirable)
NA	Continuous filament glass fibers	US ACGIH	1.0 fibers/cc ^c 5 mg/m ³ (inhalable)
	g1033 110C13	US OSHA	10 mg/m ³ (total dust)
			5 mg/m ³ (respirable fraction)

 $^{^{}a}$ The US OSHA standard for amorphous silica is: $(80 \text{ mg/m}^{3})/(\% \text{SiO2})$. The NIOSH Sampling Method 7501 for Amorphous Silica calculates the %SiO2 based on the percentage of crystalline silica in the sample. Because the percentage of crystalline silica in aerogel is 0%, the particulate limit applies.

8.2 Exposure Control

Ventilation: Local exhaust in accordance with general industrial hygiene practices is recommended to

control dust.

b US ACGIH based on Particles Not Otherwise Specified (PNOS)

^c Respirable fibers: length >5 μ m; aspect ratio \geq 3:1, as determined by the membrane filter method at 400–450X magnification (4-mm objective), using phase-contrast illumination. US NIOSH considers fibers as: length >5 μ m, width <3 μ m diameter and length: width ratios \geq 3.



Pyrogel ® XT Plus Revision Date: 12/07/11

Respiratory A properly fitted, NIOSH or CE approved respirator should be worn when ventilation is **Protection:** unavailable or inadequate to maintain airborne concentrations below applicable occupation

unavailable or inadequate to maintain airborne concentrations below applicable occupational exposure limits. A respiratory protection program that meets applicable local regulations

should be implemented whenever workplace conditions warrant use of a respirator.

Hand Protection Silica aerogels are hydrophobic (repel water) and may cause drying and irritation of the skin,

eyes, and mucous membranes. For this reason, nitrile, latex, or other impermeable gloves

should be worn when handling aerogel blankets.

Eye Protection: Safety glasses. Chemical goggles could be worn to provide greater protection from dust.

Skin Protection: Long-sleeved, long-legged work clothes are also advised. Disposable coveralls should be

considered to minimize skin exposure and track out of aerogel dusts into adjacent areas.

Work Hygienic

Practices

Keep materials packaged until just prior to use. Die cut in preference to rotary or other cutting methods. Dry vacuum with proper filtration preferred to sweeping. Wash thoroughly after using the product. Wash clothing if dust conditions present. Wash hands before eating

or drinking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Opaque maroon fabric blanket; material is hydrophobic (repels water)

Odor: No characteristic odor. Under certain conditions, such as high storage temperatures, product

may have faint ammonia-like odor.

Odor Threshold Reported ammonia threshold vary widely: 0.6 to 53 ppm

Not applicable. pH: Not applicable **Specific Gravity:** Not applicable. **Boling Point/Range: Freezing Point** Not applicable **Flash Point:** Not applicable. Flammability (solid, gas): Not applicable. **Explosive Properties:** Not applicable. Not applicable. **Oxidizing Properties: Vapor Pressure:** Not applicable. Vapor Density (air = 1) Not applicable

Solubility:Insoluble.Viscosity:Not applicable.Evaporation Rate:Not applicable

Coeffiient of water/oil

distribution

Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Prolonged exposure to temperatures above the recommended use temperature as noted

in technical data sheet. Avoid conditions that produce large quantities of dust dispersed

in air.

Materials to Avoid: Avoid strong acids and bases.

Hazardous Under recommended usage conditions, hazardous decomposition products are not

Decomposition Products expected. Hazardous decomposition products, including carbon monoxide and other

productions of combustion, may occur as a result of oxidation, heating or reaction with

another material.



Pyrogel ® XT Plus Revision Date: 12/07/11

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Dust may cause mechanical irritation and dryness to eyes and skin.

Synthetic Amorphous Silica

Oral LD50: >5,000 mg/kg **Inhalation LC50:** >2,000 mg/m³ **Dermal LD50:** >3,000 mg/kg

Eye & Skin Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental

Irritation: conditions, but may produce dryness following prolonged and repeated exposure.

Iron Oxide: Oral LD50: > 10,000 mg/kg

Aluminum Trihydrate

Oral LD50: >5,000 mg/kg (rat)
Eye Irritation: Slightly irritating
Non-irritating

CHRONIC TOXICITY

According to the manufacturer, the fiberglass in this product is considered textile grade fibrous glass and it is not classified as a carcinogen by ACGIH, IARC, NTP or OSHA. The International Agency for Research on Cancer (IARC) considers synthetic amorphous silica to be not classifiable as to its carcinogenicity to humans (Group 3).

NOTE TO SECTION 11: Toxicological information for synthetic amorphous silica is based on literature review.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Synthetic Amorphous Silica Fish: LC50 > 10,000 mg/L (Brachydanio rerio: 96 hour), Method OECD 203

Daphnia magna: EC50 > 10,000 mg/l (24 hours), Method OECD 202

Aluminum Trihydrate Fish: LC50 > 10,000 mg/L

Mobility None expected due to insoluble nature of product.

Persistence and Biodegradability Not applicable for inorganic material.

Bioaccumulative PotentialNone expected due to insoluble nature of product.

Other Adverse Effects None expected.

NOTE TO SECTION 12: Ecological information is based on literature review for synthetic amorphous silica.

Information on aluminum trihydrate based on manufacturer's information.

13. DISPOSAL CONSIDERATIONS

Dispose in an approved landfill in accordance with federal, state / provincial, and local regulation. Cover promptly to avoid blowing of dust. This product is not regulated as a hazardous waste under US RCRA regulations.

14. TRANSPORT INFORMATION

Shipping Name: Not regulated for transport

Hazard Class None
UN Number None
Packing Group None
Required Label(s) None
Marine Pollutant No
Additional Information None



Pyrogel ® XT Plus Revision Date: 12/07/11

15. REGULATORY INFORMATION

EU REGULATORY INFORMATION

Product is not classified as a dangerous material or preparation as defined in EC Directives 67/548/EEC or 1999/45/EC. Aerogel insulation blankets are considered an article, not a substance or preparation, under the REACH directive.

U.S. FEDERAL REGULATIONS

CERCLA (Comprehensive Response Compensation and Liability Act): Product is not classified as hazardous or reportable under this requirement.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Product is not classified as hazardous or reportable under this requirement.

311/312 HAZARD CATEGORIES: Materials in this product are classified as hazardous or reportable under this requirement.

313 REPORTABLE INGREDIENTS: Materials in this product are not classified as hazardous or reportable under this requirement.

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

STATE REGULATIONS: Materials in this product appear on the following state hazardous substance lists: CA, IN, KY, MA, MN, NC, NJ, OR, PA. Check individual state requirements.

CANADIAN REGULATIONS: This product has been classified according to the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR. All chemical substances in this product are included on or exempted from the Canadian Domestic Substance List (DSL). The iron oxide pigment used is on the Non-Domestic Substances List (NDSL). Amorphous silica (CAS No. 7631-86-9) is on listed on the WHMIS Ingredient Disclosure List at a concentration threshold of 1%.

16. OTHER INFORMATION

NFPA HAZARD CLASSIFICATION		HMIS HAZARD CLASSIFICATION	
Health Flammability Reactivity	1 0 0 N/A	Health Flammability Reactivity Protection	1 0 0 Please refer to Section 8
Other	N/A	Protection	Please refer to Section 8.

Synthetic Amorphous Silica Toxicity Information Reference: United Nations Environmental Programme (UNEP), Organization for Economic Cooperation & Development (OECD) Screening Information Data Set (SIDS) Initial Assessment Report, Synthetic Amorphous Silica, July 23, 2004.

Revision Summary: New product.

DISCLAIMER: The information herein is presented in good faith and believed to be accurate as the effective data given. However, no warranty, expressed or implied, is given. It is the user's responsibility to ensure that its activities comply with Federal, State or Provincial, and local laws.